

GIRTON ROLLER CONVEYOR MODEL RC

GENERAL

The Roller Conveyor may be located at either end of a Tunnel Washer, to accumulate items before or after they have been washed.

The Roller Conveyor may be optionally equipped with an automatic conveyor shut off switch, which will stop the operation of the Tunnel Washer Conveyor when items reach the end of the conveyor, indicating the system is fully loaded.

CONSTRUCTION

Stainless steel construction, including frame, rollers, and shafts. Rollers shall be fabricated of 1-5/8" OD stainless steel and positioned on 2-1/2" centers.

Side members are heavy gauge stainless steel formed channels.

Legs and roller conveyor supports are fabricated of stainless steel tubing.

The roller conveyor shall be provided with leveling devices on the legs.

The roller conveyor may be provided with or without a stainless steel drip pan underneath the roller bed.

DIMENSIONS (Please circle size desired.)

Conveyor width - 24", 30", 36", 42", 48", _____" (other)

Overall length - 2', 4', 6', 8', 10', 12', _____' (other)

RECOMMENDED SERVICES

Electrical - 1/60/115. (When automatic shut-off switch is included.)

Note: Services shall be tied into the Tunnel Washer system.

* Please note that all sub components of Girton Washers are **NON-PROPRIETARY** and **COMMERCIALY AVAILABLE** from various sources, for **FLEXIBILITY AND ECONOMY OF MAINTENANCE** throughout the life of the washer.